

ALSCO reserves the right to discontinue or modify any product line. In the unlikely event that any of the original Products are no longer available, and ALSCO at its sole discretion elects to replace the Products in lieu of repairing or refinishing the Products,ALSCO will substitute products of comparable quality. ALSCO also reserves the right to discontinue particular colors. If any of the original Product colors are not available,ALSCO will in good faith under-take to substitute a currently available color that most closely matches the original color. Since a color or gloss variance may occur between replacement Product(s) and the originally installed Product(s) due to the normal weathering and aging of the originally installed Product(s), this will not be indicative of a defect in either the replaced, repaired, or refinished Product(s) or in the originally installed Product(s).

THE WARRANTIES SET FORTH IN THIS CERTIFICATE ARE THE ONLY WARRANTIES EXTENDED BYALSCO IN CONNECTION WITH YOUR ALSCO PRODUCT(S) AND ARE IN LIEU OF ALL OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING, BUT NOT LIMITED TO,THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

THE REMEDIES SET FORTH IN THIS CERTIFICATE SHALL CONSTITUTE YOUR EXCLUSIVE REMEDIESANDALSCO'S SOLE LIABILITY. IN NO EVENT SHALL ALSCO BE LIABLE FOR SPECIAL, EXEMPLARY, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES FOR THE BREACH OF ANY EXPRESS OR IMPLIED WARRANTIES OR ANY OTHER CLAIM,WHETHER ARISING IN TORT, BY CONTRACT OR PURSUANT TO STATUTE, IN CONNECTION WITH YOUR PRODUCT(S).

Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above exclusion or limitation may not apply to you.This Warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.

#### **CONDITIONS THAT AREN'T COVERED BY THIS WARRANTY**

This Warranty covers only the manufacturing defects described in this Certificate and only if they arise from ordinary wear during normal and proper use and service. It does not cover, for example, defects attributable to causes or occurrences beyond ALSCO's control and unrelated to the manufacturing process, including, but not limited to faulty or improper installation (e.g., waving, buckling, oil canning, other distortions), lap abrasion, warping or distortion due to excessive heat sources (e.g., barbecue grills) or excessive reflective heat sources (e.g., window reflection), installation of Product(s) in contact with dissimilar materials as discussed below, normal weathering, oxidation, exposure to cor'osive atmospheres (such as those contaminated with salt or salt spray, acid rain, harmful chemicals, fumes or vapors), air pollution, mold, mildew, unreasonable use, misuse, physical abuse, accidental damage, vandalism, use of incompatible accessories, fire, flood, earthquake, lightning, ice or windstorms, hail or other acts of God, crazing or cracking of the Product's paint due to field forming in cold temperatures, wind-borne objects, building settlement or shrinkage or structural failures (including walls and foundations), or the use of harmful cleaning compounds or pesticides.

Fading and color change are not covered by this Warranty.Weathering (i.e., exposure to sunlight and extremes of weather and temperature) and the normal aging process will cause any colored surface to fade, darken, chalk or acquire a surface accumulation of dirt, mold, mildew or stains.The severity of these conditions depends on air quality, the geographic location of your Property and other local conditions (including unequal exposure of the installed Product(s) to the sun and other elements) over which ALSCO has no control.

Your Product(s) are not intended for use within one (1) mile of any body of salt water, and this Warranty will not apply to any Product(s) installed within one (1) mile of any body of salt water.

Direct contact of aluminum Product(s) with certain dissimilar materials or contact with the water run-off from such materials is likely to result in corrosion, which is not covered by this Warranty. Therefore, care should be exercised to avoid contact of aluminum with any corrosive materials during installation including, but not limited to: pretreated lumber, concrete, masonry cement, stucco, salt, corrosive chemicals, dissimilar metals (copper, zinc, steel, etc.), and roofing systems made with metallic granules of such dissimilar metals.

*(Continued on reverse side)*

#### **OTHER LIMITATIONS**

1. This warranty applies only to Product(s) installed on property located with the 48 contiguous states of the U.S.A.
2. This Warranty covers only genuine ALSCO Products and it is the Property owner's responsibility to verify that the Products are ALSCO Products by verifying that the first six digits of the UPC number on the label are 757543.
3. Products that have been refinished or painted in any way without the written authorization of ALSCO are not covered by this warranty.
4. There are no warranties on the Products or available remedies other than those set forth in this Warranty. ALSCO is not liable to you for breach of any other oral or written express warranties, if any, given to you by, for example, contractors, applicators, dealers or distributors of the Products.
5. Certain Products are designed for use as water diverters and small flashings and should not to be used as roofing materials.
6. This Warranty applies to only the Products listed and does NOT cover other products sold by ALSCO, including, for example, rain gutters, gutter leaf protection devices, downspouts or accessories used in their installation.

#### **CARE AND MAINTENANCE INSTRUCTIONS**

##### **NORMAL CONDITIONS**

The finish on these Products, like any other colored or painted surface, is susceptible to chalking and some degree of color change due to normal weathering and, also, to dirt accumulation, depending on the atmosphere to which your home is subjected. Under normal conditions, objectionable superficial surface dirt can be removed by washing with a garden hose and a soft-bristled brush. While weathering occurs through exposure to sunlight or weather extremes, the factory applied finish resists the associated problems of peeling, chipping and flaking. In addition to the longer term period of resistance to chipping, peeling and flaking, the colored coatings are formulated to resist fading due to normal weathering for a reasonable period of time.

The finish gradually releases microscopic particles of pigment in the form of a light powder. This "controlled chalking" is the best way for exposed surface coatings to weather, while providing a self-cleaning feature which helps eliminate loose surface dirt during normal rainfall.

##### **UNUSUAL CONDITIONS**

In industrial areas where a more thorough cleaning is necessary or for stains resulting from tree sap, insecticides, chimney fumes, etc., the finish should be washed with a sponge or soft-bristled brush and a solution of detergent and water (1/3 cup Tide per gallon of water, for example). Immediately rinse surfaces thoroughly with a garden hose. Avoid vigorous rubbing as it can cause undesirable glossy areas over the finish. A rotary soft-bristled brush equipped with extension handle is handy for reaching high areas. To minimize streaking, wash from bottom to top.

In some locales mildew may appear as black spots in the accumulated dirt. Mildew may be removed with the following solution. The solution may be sprayed or sponged on or applied with a soft-bristled brush and allowed to remain for 15 to 20 minutes and then rinsed with a hose. An adequate rinse should be assured to cleanse the finish and also further dilute the solution so as not to harm shrubbery. It is also advisable to test your solution or cleaner on an inconspicuous area before application to large areas.

##### **SOLUTION:**

- 1 /3 cup detergent (Tide, for example)\*
- 2/3 cup trisodium phosphate (Soilax, for example)\*
- 1 qt. sodium hypochlorite 5% solution (Clorox, for example)\*
- 3 qts. water

'CAUTION: Greater concentrations may cause damage to the finish. Do not use abrasive or solvent type cleaners or paint removers. Avoid skin contact or getting the solution in eyes. Always read and follow cleaning compound manufacturers' instructions.

##### **CAULKING COMPOUNDS AND TAR**

Mineral spirits may be used, in reasonable amounts, to remove caulking compounds or tar from the finish. Rinse immediately with clear water.

Copyright© 2004 ALSCO Metals Corporation. ALSCO Metals Corporation reserves the right as its option, without liability to change, and/or delete products or colors at any time without notice. WAR2-GUT-0904 Printed in U.S.A.